

WEROTECH-SB | SIMPLYBLUE

TRANSFER ROLLER COVERING FOR SOLVENT FREE LAMINATING MACHINES

PRODUCT PORTFOLIO

Compound	Sh A	Color	EL. Properties	Max.°C	MO	O ₃	ELA	E/K	AB
WEROTECH-SB									
N852-24	85	ocean blue	isolating	120	2	1	3	2	2

● = Chemical Resistance : MO = Mineral Oil | O₃ = Ozone | E/K = Esters/Ketones

1 = resistant | 2 = resistant with restrictions | 3 = not resistant

● = Physical Properties : ELA = Elasticity | AB = Abrasion Resistance

1 = very good | 2 = good | 3 = moderate

Electric (EL) Properties : Conductive < 10⁴ Ω | Dissipative < 10⁸ Ω | Isolating > 10¹⁴ Ω.

The electrical resistance was tested on a laboratory sample and does not match the value of the rubberized roller.

Features:

- ✓ Optimized surface tension property to ensure an evenly distributed glue onto the substrate, resulting in a more precise and uniform coating.
- ✓ Improved coating quality, that not only enhances the appearance of the final product but also ensures the integrity and strength of the lamination
- ✓ Resistant to wear and tear, making it ideal for use in high-volume production environments

Fields of application:

- ✓ Food Packaging
- ✓ Medical Packaging
- ✓ Industrial Packaging

Liability exclusion

■ The above information is based on our knowledge and experience under normal conditions, assuming the product is stored and used properly. This data is understood as the characterization of the material properties and not as minimum values in terms of specification. Technical changes reserved.